

ASX-612B/612BT

ASX-312B/312BT



High fidelity 2-Way speaker system in compact & attractive Black or White plastic housing. The suffix B & BT denote Black cabinet, and W & WT denote White cabinet. Ideal for various indoor and outdoor (under eaves) applications in Airports, Banks, Schools, Hotels, Restaurants, Lounges, Hospitals, Showrooms etc.

- Comprises of a Water Resistant PP coated cone Woofer, a Titanium Dome Tweeter and a 2-way Crossover Network.
- ASX-612B, ASX-612W and ASX-312B, ASX-312W are low impedance 8Ω speakers.
- ASX-612BT and ASX-612WT are for use on 100V line with power taps of 60W, 40W, 30W, 20W & 10W.
- ASX-312BT and ASX-312WT are for use on 100V line with power taps of 30W, 20W, 15W, 10W & 5W.
- Easy power tap selection through a slotted rotary switch knob at the rear.
- 'U' type bracket for convenient & firm mounting of the wall speaker.

SPECIFICATIONS

	ASX-612B/612BT	ASX-312B/312BT
POWER RATING	60W RMS/90W Max.	30W RMS/45W Max.
POWER TAPS	60W, 60/40/30/20/10W	30W, 30/20/15/10/5W
IMPEDANCE/VOLTAGE	8Ω / 100V	8Ω / 100V
FREQUENCY RESPONSE	50-20,000Hz	75-20,000Hz
SPL at 1kHz (1W/1m)	87dB	87dB
SPEAKER	Woofer 163mm (6 1/2"), Tweeter 25mm (1")	Woofer 100mm (4"), Tweeter 25mm (1")
DIMENSIONS	W215 × H310 × D175 mm	W180 × H248 × D140 mm
WEIGHT	3.22kg/3.80kg	2.45kg/2.92kg

Design and Specifications are subject to change without notice owing to continuous product up-gradation. Technical specifications are subject to production tolerances. We cannot be held responsible for printing errors, should they occur. AHUJA is a registered trademark of Ahuja Radios in India and other countries. © Copyright Ahuja Radios, 2017. All rights reserved. Any unauthorized reproduction or use of logos, images or design elements is strictly prohibited by law. No part of this compilation may be reproduced in any manner or translated without written permission.

TRUSOUND PVT. LTD.

C-89, Sector IV, Noida, Gautam Budh Nagar-201 301 (UP), Regd. Office : 125E, Okhla Industrial Estate, New Delhi-110 020
Tel.: +91-120-4665665 Fax : +91-120-4665621 E-mail: trusoundsupport@airtelmail.in