



## SPX-710 600 WATTS



Compact and powerful 600 Watts Professional 2-Way PA Loudspeaker with excellent LF response, exceptional efficiency and unmatched intelligibility of sound. Two 30.48 cm (12") high performance LF loudspeakers and a high power titanium compression horn driver housed in an acoustically treated bass reflex trapezoidal painted enclosure. Strong steel grille for speaker protection. Heavy duty metal handles allow ease of mobility and transportation. Suitable for both indoor and outdoor sound reinforcement applications. Ideal for Auditoria... DJs... Live...Concerts... Discos... etc.

SPECIFICATIONS	SPX-710
POWER RATING	600W RMS/1200W Programme
CONFIGURATION	Two Way
FREQUENCY RESPONSE	40-20,000Hz
LOW FREQUENCY SPEAKER	2 × 305 mm (12"), Ø76.2mm (3") Voice coil
HIGH FREQUENCY UNIT	Dynamic Horn 177.8 mm (7") × 304.8 mm (16")
SPL at (1W/1m)	104dB
MAX. RATED SPL	131dB
NOMINAL IMPEDANCE	4Ω
CROSSOVER FREQUENCY	4kHz
PORT	Free Flow Flared
INPUT CONNECTORS	2 Nos. of Speakon Sockets
DIMENSIONS	W405 × H1016 × D378 mm
WEIGHT	40.80kg

