PA Cabinet Loudspeakers - Subwoofer









SWX-1010 is a compact and powerful super power SUBWOOFER with exceptional distortion-free low frequency response. It is fitted with a 45.72 cm (18") LF driver having 12.7 cm (5") inside/outside voice coil wound on a polyimide fibre glass former. The speaker has an aluminium demodulating ring for better heat dissipation and a specially treated cone for water splash resistance. The cabinet is rugged and specially braced to withstand intense vibrations. The enclosure is fitted with four heavy duty handles, a recessed terminal plate and four indexed feet for ease of stacking. The strong metal grille protects the speaker from unavoidable strokes.

SPECIFICATIONS	SWX-1010
power RATING	1000W RMS/2000W Programme
CONFIGURATION	One Way
FREQUENCY RESPONSE	36-200Hz
LOW FREQUENCY SPEAKER	1 x 457.2 mm (18") with
	Ø127 mm (5") Inside/Outside Wound Voice Coil
SPL at (1W/1m)	99dB
MAX. RATED SPL	129dB
NOMINAL IMPEDANCE	8Ω
PORT	Free Flow Flared
INPUT CONNECTORS	Terminal Strip + Speakon
DIMENSIONS	W538 \times H710 \times D700 mm
WEIGHT	55.20kg